

FOLLOW THE REGULARIZED LEADER

Advanced Machine Learning

- To overcome the shortcomings of the FTL algorithm, one can incorporate a regularization function $\psi : \mathcal{A} \rightarrow \mathbb{R}_+$ into the action choice of FTL, which leads to more stability.

Follow the regularized leader

- To be more precise, let for $t \geq 1$


$$a_t^{\text{FTRL}} \in \arg \min_{a \in \mathcal{A}} \left(\psi(a) + \sum_{s=1}^{t-1} \ell_s(a, z_s) \right),$$

Learning goals

(Technical side note: if there are more than one minimum, then one of them is chosen.)

then the algorithm choosing a_t^{FTRL} in time step t is called the **Follow the regularized leader (FTRL) algorithm**.

- Get to know FTRL and its alternative for FTL
- See a suitable regularization for OLO problems



FOLLOW THE REGULARIZED LEADER

- To overcome the shortcomings of the FTL algorithm, one can incorporate a regularization function $\psi : \mathcal{A} \rightarrow \mathbb{R}_+$ into the action choice of FTL, which leads to more stability.
- To be more precise, let for $t \geq 1$

$$a_t^{\text{FTRL}} \in \arg \min_{a \in \mathcal{A}} \left(\psi(a) + \sum_{s=1}^{t-1} \ell(a, z_s) \right),$$

(Technical side note: if there are more than one minimum, then one of them is chosen.)

then the algorithm choosing a_t^{FTRL} in time step t is called the **Follow the regularized leader (FTRL) algorithm**:

- Interpretation:* The algorithm predicts a_t as the element in \mathcal{A} , which minimizes the regularization function plus the cumulative loss so far over the previous $t - 1$ time periods.



FOLLOW THE REGULARIZED LEADER

- To overcome the shortcomings of the FTL algorithm, one can incorporate a regularization function $\psi : \mathcal{A} \rightarrow \mathbb{R}_+$ into the action choice of FTL, which leads to more stability.
- To be more precise, let for $t \geq 1$

$$a_t^{\text{FTL}} a_t^{\text{FTRL}} \in \arg \min_{a \in \mathcal{A}} \left(\psi(a) + \sum_{s=1}^{t-1} \langle a, z_s \rangle \right),$$

(Technical side note: if there are more than one minimum, then one of them is chosen.)

then the algorithm choosing a_t^{FTRL} in time step t is called the **Follow the regularized leader (FTRL) algorithm**:

- Interpretation:** The algorithm predicts a_t as the element in \mathcal{A} , which minimizes the regularization function plus the cumulative loss so far over the previous $t - 1$ time periods.
- Obviously, the behavior of the FTRL algorithm is depending heavily on the choice of the regularization function ψ . If $\psi \equiv 0$, then FTRL equals FTL.



REGULARIZATION IN ONLINE LEARNING VS. BATCH LEARNING

- To overcome the shortcomings of the FTL algorithm, one can incorporate a regularization function $\psi: \mathcal{A} \rightarrow \mathbb{R}$ into the optimization objective of FTL, which leads to more stability.
- Note that in the batch learning scenario, the learner seeks to optimize an objective function which is the sum of the training loss and a regularization function:
- To be more precise, let for $t \geq 1$

$$a_t^{\text{FTRL}} \in \arg \min_{\theta \in \mathbb{R}^p} \left(\ell(y^{(t)}, \theta) + \sum_{i=1}^{t-1} \ell(y^{(i)}, \theta) + \lambda \psi(\theta) \right),$$

(Technical side note: if there are more than one minimum, then one of them is chosen.)

then the algorithm choosing a_t^{FTRL} in time step t is called the **Follow the regularized leader** (FTRL) algorithm.

- Interpretation:* The algorithm predicts a_t as the element in \mathcal{A} , which minimizes the regularization function plus the cumulative loss so far over the previous $t - 1$ time periods.
- Obviously, the behavior of the FTRL algorithm is depending heavily on the choice of the regularization function ψ . If $\psi \equiv 0$, then FTRL equals FTL.



REGULARIZATION IN ONLINE LEARNING VS. BATCH LEARNING

- Note that in the batch learning scenario, the learner seeks to optimize an objective function which is the sum of the training loss and a regularization function:

$$\min_{\theta \in \mathbb{R}^p} \sum_{i=1}^n L(y^{(i)}, \theta) + \lambda \psi(\theta),$$

where $\lambda \geq 0$ is some regularization parameter.

- Here, the regularization function is part of the whole objective function, which the learner seeks to minimize.



REGULARIZATION IN ONLINE LEARNING VS. BATCH LEARNING

- Note that in the batch learning scenario, the learner seeks to optimize an objective function which is the sum of the training loss and a regularization function:

$$\min_{\theta \in \mathbb{R}^p} \sum_{i=1}^n L(y^{(i)}, \theta) + \lambda \psi(\theta),$$

where $\lambda \geq 0$ is some regularization parameter.

- Here, the regularization function is part of the whole objective function, which the learner seeks to minimize.
- However, in the online learning scenario the regularization function does (usually) not appear in the regret the learner seeks to minimize, but the regularization function is only part of the action/decision rule at each time step.



REGRET ANALYSIS OF FTRL: A HELPFUL LEMMA

BATCH LEARNING

- **Lemma:** Let $a_1^{\text{FTRL}}, a_2^{\text{FTRL}}, \dots$ be the sequence of actions coming used by the FTRL algorithm for the environmental data sequence z_1, z_2, \dots . Then, for all $\tilde{a} \in \mathcal{A}$ we have
- the sum of the training loss and a regularization function:

$$R_T^{\text{FTRL}}(\tilde{a}) = \sum_{t=1}^T ((a_t^{\text{FTRL}}, z_t) - (\tilde{a}, z_t)) \\ \min_{\theta \in \mathbb{R}^p} \sum_{i=1}^T L(y^{(i)}, \theta) + \lambda \psi(\theta), \\ \leq \psi(\tilde{a}) - \psi(a_1^{\text{FTRL}}) + \sum_{t=1}^T ((a_t^{\text{FTRL}}, z_t) - (a_{t+1}^{\text{FTRL}}, z_t)).$$

where $\lambda \geq 0$ is some regularization parameter.

- Here, the regularization function is part of the whole objective function, which the learner seeks to minimize.
- However, in the online learning scenario the regularization function does (usually) not appear in the regret the learner seeks to minimize, but the regularization function is only part of the action/decision rule at each time step.



REGRET ANALYSIS OF FTRL: A HELPFUL LEMMA

- **Lemma:** Let $a_1^{\text{FTRL}}, a_2^{\text{FTRL}}, \dots$ be the sequence of actions coming used by the FTRL algorithm for the environmental data sequence z_1, z_2, \dots . Then, for all $\tilde{a} \in \mathcal{A}$ we have

$$\begin{aligned} R_T^{\text{FTRL}}(\tilde{a}) &= \sum_{t=1}^T ((a_t^{\text{FTRL}}, z_t) - (\tilde{a}, z_t)) \\ &\leq \underbrace{1}(\tilde{a}) - \underbrace{1}(a_1^{\text{FTRL}}) + \sum_{t=1}^T ((a_t^{\text{FTRL}}, z_t) - (a_{t+1}^{\text{FTRL}}, z_t)). \end{aligned}$$

- *Interpretation:* the regret of the FTRL algorithm is bounded by the difference of cumulated losses of itself compared to its one-step lookahead cheater version and an additional regularization difference term.

⇒ We have seen an analogous result for FTL!

(The proof is similar.)



FTRL FOR ONLINE LINEAR OPTIMIZATION LEMMA

- In the following, we analyze the FTRL algorithm for the linear loss $L(a, z) = a^T z$ for online linear optimization (OLO) problems.
- Then, for all $\tilde{a} \in A$, we have:

$$R_T^{\text{FTRL}}(\tilde{a}) = \sum_{t=1}^T \left(L(\tilde{a}_t^{\text{FTRL}}, z_t) - \frac{1}{2\eta} \|a_t^{\text{FTRL}}\|_2^2 \right) \frac{a_t^{\text{FTRL}}}{2\eta},$$

where η is some positive scalar, the regularization magnitude.

$$\leq \psi(\tilde{a}) - \psi(a_1^{\text{FTRL}}) + \sum_{t=1}^T (L(a_t^{\text{FTRL}}, z_t) - L(a_{t+1}^{\text{FTRL}}, z_t)).$$

- Interpretation:* the regret of the FTRL algorithm is bounded by the difference of cumulated losses of itself compared to its one-step lookahead cheater version and an additional regularization difference term.

⇒ We have seen an analogous result for FTL!

(The proof is similar.)



FTRL FOR ONLINE LINEAR OPTIMIZATION

- In the following, we analyze the FTRL algorithm for the linear loss $\ell(a; z) = a^\top z$ for online linear optimization (OLO) problems.
- For this purpose, the squared L2-norm regularization will be used:

$$\psi(a) = \frac{1}{2\eta} \|a\|_2^2 = \frac{a^\top a}{2\eta},$$

where η is some positive scalar, the *regularization magnitude*.

- It is straightforward to compute that if $\mathcal{A} = \mathbb{R}^d$, then

$$a_t^{\text{FTRL}} = -\eta \sum_{s=1}^{t-1} z_s.$$



FTRL FOR ONLINE LINEAR OPTIMIZATION

- In the following, we analyze the FTRL algorithm for the linear loss $(a, z_t) = a^T z_t$ for online linear optimization (OLO) problems.
- For this purpose, the squared L2-norm regularization will be used:

$$\psi(a) = \frac{1}{2\eta} \|a\|_2^2 = \frac{a^T a}{2\eta},$$

where η is some positive scalar, the *regularization magnitude*.

- It is straightforward to compute that if $\mathcal{A} = \mathbb{R}^d$, then

$$a_t^{\text{FTRL}} = -\eta \sum_{s=1}^{t-1} z_s.$$

- Hence, in this case we have for the FTRL algorithm the following update rule

$$a_{t+1}^{\text{FTRL}} = a_t^{\text{FTRL}} - \eta z_t, \quad t = 1, \dots, T-1.$$



FTRL FOR ONLINE LINEAR OPTIMIZATION

- In the following, we analyze the FTRL algorithm for the linear loss $(a, z_t) = a^T z_t$ for online linear optimization (OLO) problems.
- For this purpose, the squared L2-norm regularization will be used:

$$\psi(a) = \frac{1}{2\eta} \|a\|_2^2 = \frac{a^T a}{2\eta},$$

where η is some positive scalar, the *regularization magnitude*.

- It is straightforward to compute that if $\mathcal{A} = \mathbb{R}^d$, then

$$a_t^{\text{FTRL}} = -\eta \sum_{s=1}^{t-1} z_s.$$

- Hence, in this case we have for the FTRL algorithm the following update rule

$$a_{t+1}^{\text{FTRL}} = a_t^{\text{FTRL}} - \eta z_t, \quad t = 1, \dots, T-1.$$

Interpretation: $-z_t$ is the *direction* in which the update of a_t^{FTRL} to a_{t+1}^{FTRL} is conducted with *step size* η in order to reduce the loss.



ONLINE THEORETICAL GUARANTEES

- **Proposition:** Using the FTRL algorithm with the squared L2-norm regularization on any online linear optimization (OLO) problem with $\mathcal{A} \subset \mathbb{R}^d$ leads to a regret of FTRL with respect to any action $\tilde{a} \in \mathcal{A}$ of

$$R_T^{\text{FTRL}}(\tilde{a}) \leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2.$$

where η is some positive scalar, the *regularization magnitude*.

- It is straightforward to compute that if $\mathcal{A} = \mathbb{R}^d$, then

$$a_t^{\text{FTRL}} = -\eta \sum_{s=1}^{t-1} z_s.$$

- Hence, in this case we have for the FTRL algorithm the following update rule

$$a_{t+1}^{\text{FTRL}} = a_t^{\text{FTRL}} - \eta z_t, \quad t = 1, \dots, T-1.$$

Interpretation: $-z_t$ is the *direction* in which the update of a_t^{FTRL} to a_{t+1}^{FTRL} is conducted with *step size* η in order to reduce the loss.



FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proposition:** Using the FTRL algorithm with the squared L2-norm regularization on any online linear optimization (OLO) problem with $\mathcal{A} \subset \mathbb{R}^d$ leads to a regret of FTRL with respect to any action $\tilde{a} \in \mathcal{A}$ of

$$R_T^{\text{FTRL}}(\tilde{a}) \leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2.$$



- We will show the result only for the case $\mathcal{A} = \mathbb{R}^d$.
- For the more general case, where \mathcal{A} is a strict subset of \mathbb{R}^d , we need a slight modification of the update formula above:

$$a_t^{\text{FTRL}} = \Pi_{\mathcal{A}} \left(-\eta \sum_{i=1}^{t-1} z_i \right) = \arg \min_{a \in \mathcal{A}} \left\| a - \eta \sum_{i=1}^{t-1} z_i \right\|_2^2.$$

In words, the action of the FTRL algorithm has to be projected onto the set \mathcal{A} . Here, $\Pi_{\mathcal{A}} : \mathbb{R}^d \rightarrow \mathcal{A}$ is the projection onto \mathcal{A} .

(The proof is essentially the same, except that the Cauchy-Schwarz inequality is used in between.)

FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proposition:** Using the FTRL algorithm with the squared L2-norm regularization on any online linear optimization (OLO) problem with $\mathcal{A} \subset \mathbb{R}^d$ leads to a regret of FTRL with respect to any action $\bar{a} \in \mathcal{A}$ of

$$\text{Reminder (1): } R_T^{\text{FTRL}}(\bar{a}) \leq \psi(\bar{a}) - \psi(a_1^{\text{FTRL}}) + \sum_{t=1}^T ((a_t^{\text{FTRL}}, z_t) - (a_{t+1}^{\text{FTRL}}, z_t)).$$

$$\text{Reminder (2): } R_T^{\text{FTRL}}(\bar{a}) \leq \frac{1}{2\eta} \|\bar{a}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2 - 1.$$

- For sake of brevity, we write a_1, a_2, \dots for $a_1^{\text{FTRL}}, a_2^{\text{FTRL}}, \dots$
- We will show the result only for the case $\mathcal{A} = \mathbb{R}^d$.
- For the more general case, where \mathcal{A} is a strict subset of \mathbb{R}^d , we need a slight modification of the update formula above:

$$a_t^{\text{FTRL}} = \Pi_{\mathcal{A}} \left(-\eta \sum_{i=1}^{t-1} z_i \right) = \arg \min_{a \in \mathcal{A}} \left\| a - \eta \sum_{i=1}^{t-1} z_i \right\|_2^2.$$

In words, the action of the FTRL algorithm has to be projected onto the set \mathcal{A} . Here, $\Pi_{\mathcal{A}} : \mathbb{R}^d \rightarrow \mathcal{A}$ is the projection onto \mathcal{A} .

(The proof is essentially the same, except that the Cauchy-Schwarz inequality is used in between.)



FTRL FOR OLO: THEORETICAL GUARANTEES

- Proof:

$$\text{Reminder (1): } R_T^{\text{FTRL}}(\bar{a}) \leq \psi(\bar{a}) - \psi(a_1) + \sum_{t=1}^{T-1} ((a_t^{\text{FTRL}}, z_t) - (a_{t+1}^{\text{FTRL}}, z_t)).$$

$$\text{Reminder (2): } a_{t+1}^{\text{FTRL}} = a_t^{\text{FTRL}} - \eta z_t, \quad t = 1, \dots, T-1.$$

- For sake of brevity, we write a_1, a_2, \dots for $a_1^{\text{FTRL}}, a_2^{\text{FTRL}}, \dots$

- With this,

$$\begin{aligned} R_T^{\text{FTRL}}(\bar{a}) &\leq \psi(\bar{a}) - \psi(a_1) + \sum_{t=1}^{T-1} ((a_t, z_t) - (a_{t+1}, z_t)) && \text{(Reminder (1))} \\ &\leq \frac{1}{2\eta} \|\bar{a}\|_2^2 + \sum_{t=1}^{T-1} (a_t^\top z_t - a_{t+1}^\top z_t) \quad (\psi(a_1) \geq 0 \text{ and definition of } \psi) \\ &= \frac{1}{2\eta} \|\bar{a}\|_2^2 + \sum_{t=1}^{T-1} (a_t^\top - a_{t+1}^\top) z_t && \text{(Distributivity)} \\ &= \frac{1}{2\eta} \|\bar{a}\|_2^2 + \eta \sum_{t=1}^{T-1} \|z_t\|_2^2. && \text{(Reminder (2))} \end{aligned}$$

□



FTRL FOR OLO: THEORETICAL GUARANTEES

- Interpretation of the terms in the proposition, i.e., of

$$\text{Reminder (1): } R_T^{\text{FTRL}}(\tilde{a}) \leq \psi(\tilde{a}) + \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \eta \sum_{t=1}^T \sum_{i=1}^I \|z_t\|_2^2 \cdot (L(a_t^{\text{FTRL}}, z_t) - L(a_{t+1}^{\text{FTRL}}, z_t)).$$

$$\text{Reminder (2): } a_{t+1}^{\text{FTRL}} = a_t^{\text{FTRL}} - \eta z_t, \quad t = 1, \dots, T-1.$$

- For sake of brevity, we write a_1, a_2, \dots for $a_1^{\text{FTRL}}, a_2^{\text{FTRL}}, \dots$

- With this,

$$\begin{aligned} R_T^{\text{FTRL}}(\tilde{a}) &\leq \psi(\tilde{a}) - \psi(a_1) + \sum_{t=1}^T (L(a_t, z_t) - L(a_{t+1}, z_t)) && \text{(Reminder (1))} \\ &\leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \sum_{t=1}^T (a_t^\top z_t - a_{t+1}^\top z_t) && (\psi(a_1) \geq 0 \text{ and definition of } \psi) \\ &= \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \sum_{t=1}^T (a_t^\top - a_{t+1}^\top) z_t && \text{(Distributivity)} \\ &= \frac{1}{2\eta} \|\tilde{a}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2. && \text{(Reminder (2))} \end{aligned}$$

□



FTRL FOR OLO: THEORETICAL GUARANTEES

- Interpretation of the terms in the proposition, i.e., of

$$R_T^{\text{FTRL}}(\tilde{\mathbf{a}}) \leq \frac{1}{2\eta} \|\tilde{\mathbf{a}}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2 :$$

- $\|\tilde{\mathbf{a}}\|_2^2$ represents a *bias term*: The regret upper bound of FTRL is always biased by the term $\|\tilde{\mathbf{a}}\|_2^2$. The impact of the bias term can be reduced by a higher regularization magnitude, i.e., a higher choice of η .



FTRL FOR OLO: THEORETICAL GUARANTEES

- Interpretation of the terms in the proposition, i.e., of

$$R_T^{\text{FTRL}}(\tilde{\mathbf{a}}) \leq \frac{1}{2\eta} \|\tilde{\mathbf{a}}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2 :$$

- $\|\tilde{\mathbf{a}}\|_2^2$ represents a *bias term*: The regret upper bound of FTRL is always biased by the term $\|\tilde{\mathbf{a}}\|_2^2$. The impact of the bias term can be reduced by a higher regularization magnitude, i.e., a higher choice of η .
- $\sum_{t=1}^T \|z_t\|_2^2$ represents a *"variance" term*: The more the environment data z_t varies, the larger this term. Hence, for a high variance a smaller regularization magnitude is needed, i.e., a smaller choice of η .



FTRL FOR OLO: THEORETICAL GUARANTEES

- Interpretation of the terms in the proposition, i.e., of

$$R_T^{\text{FTRL}}(\tilde{\mathbf{a}}) \leq \frac{1}{2\eta} \|\tilde{\mathbf{a}}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2 :$$

- $\|\tilde{\mathbf{a}}\|_2^2$ represents a *bias term*: The regret upper bound of FTRL is always biased by the term $\|\tilde{\mathbf{a}}\|_2^2$. The impact of the bias term can be reduced by a higher regularization magnitude, i.e., a higher choice of η .
 - $\sum_{t=1}^T \|z_t\|_2^2$ represents a *"variance" term*: The more the environment data z_t varies, the larger this term. Hence, for a high variance a smaller regularization magnitude is needed, i.e., a smaller choice of η .
- Thus, we have a trade-off for the optimal choice of η : Making η large, leads to a smaller bias but at the expense of a higher variance and making η small leads to a smaller variance at the expense of a higher bias.



FTRL FOR OLO: THEORETICAL GUARANTEES

- Interpretation of the terms in the proposition, i.e., of


$$R_T^{\text{FTRL}}(\tilde{\mathbf{a}}) \leq \frac{1}{2\eta} \|\tilde{\mathbf{a}}\|_2^2 + \eta \sum_{t=1}^T \|z_t\|_2^2 :$$

- $\|\tilde{\mathbf{a}}\|_2^2$ represents a *bias term*: The regret upper bound of FTRL is always biased by the term $\|\tilde{\mathbf{a}}\|_2^2$. The impact of the bias term can be reduced by a higher regularization magnitude, i.e., a higher choice of η .
 - $\sum_{t=1}^T \|z_t\|_2^2$ represents a *"variance" term*: The more the environment data z_t varies, the larger this term. Hence, for a high variance a smaller regularization magnitude is needed, i.e., a smaller choice of η .
 - Thus, we have a trade-off for the optimal choice of η : Making η large, leads to a smaller *bias* but at the expense of a higher *variance* and making η small leads to a smaller *variance* at the expense of a higher *bias*.
- ⇒ With the right choice of η , we can prevent the instability of FTRL for an online linear optimization (OLO) problem.



FTRL FOR OLO: THEORETICAL GUARANTEES

- Under certain assumptions we can balance the trade-off induced by the bias and the variance by choosing η appropriately.




- $\|\tilde{\mathbf{a}}\|_2^2$ represents a *bias term*: The regret upper bound of FTRL is always biased by the term $\|\tilde{\mathbf{a}}\|_2^2$. The impact of the bias term can be reduced by a higher regularization magnitude, i.e., a higher choice of η .
- $\frac{1}{2\eta}$ represents a *variance term*: The more the environment data \mathbf{z}_t varies, the larger this term. Hence, for a high variance a smaller regularization magnitude is needed, i.e., a smaller choice of η .

- Thus, we have a trade-off for the optimal choice of η : Making η large, leads to a smaller bias but at the expense of a higher variance and making η small leads to a smaller variance at the expense of a higher bias.

⇒ With the right choice of η , we can prevent the instability of FTRL for an online linear optimization (OLO) problem.

FTRL FOR OLO: THEORETICAL GUARANTEES

- Under certain assumptions we can balance the trade-off induced by the bias and the variance by choosing η appropriately.




- Corollary:** Suppose we use the FTRL algorithm with the squared L2-norm regularization on an online linear optimization problem with $\mathcal{A} \subset \mathbb{R}^d$ such that
 - $\sup_{\tilde{a} \in \mathcal{A}} \|\tilde{a}\|_2 \leq B$ for some finite constant $B > 0$,
 - $\sup_{z \in \mathcal{Z}} \|z\|_2 \leq V$ for some finite constant $V > 0$.



FTRL FOR OLO: THEORETICAL GUARANTEES

- Under certain assumptions we can balance the trade-off induced by the bias and the variance by choosing η appropriately.



- Corollary:** Suppose we use the FTRL algorithm with the squared L2-norm regularization on an online linear optimization problem with $\mathcal{A} \subset \mathbb{R}^d$ such that
 - $\sup_{\tilde{\mathbf{a}} \in \mathcal{A}} \|\tilde{\mathbf{a}}\|_2 \leq B$ for some finite constant $B > 0$,
 - $\sup_{\mathbf{z} \in \mathcal{Z}} \|\mathbf{z}\|_2 \leq V$ for some finite constant $V > 0$.


Then, by choosing the step size η for FTRL as $\eta = \frac{B}{V\sqrt{2T}}$ it holds that

$$R_T^{\text{FTRL}} \leq BV\sqrt{2T}.$$



FTRL FOR OLO: THEORETICAL GUARANTEES

- Under certain assumptions we can balance the trade-off induced by the bias and the variance by choosing η appropriately.



- Corollary:** Suppose we use the FTRL algorithm with the squared L2-norm regularization on an online linear optimization problem with $\mathcal{A} \subset \mathbb{R}^d$ such that
 - $\sup_{\tilde{a} \in \mathcal{A}} \|\tilde{a}\|_2 \leq B$ for some finite constant $B > 0$,
 - $\sup_{z \in \mathcal{Z}} \|z\|_2 \leq V$ for some finite constant $V > 0$.Then, by choosing the step size η for FTRL as $\eta = \frac{B}{V\sqrt{2T}}$ it holds that


$$R_T^{\text{FTRL}} \leq BV\sqrt{2T}.$$

- Note that the (optimal) parameter η depends on the time horizon T , which is oftentimes not known in advance. However, there are some tricks (i.e., the *doubling trick*), which can help in such cases.

FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proof:** certain assumptions we can balance the trade-off induced by the bias and the variance by choosing η appropriately.

$$R_T^{FTRL}(\tilde{a}) \leq \frac{1}{2\eta} \|\tilde{a}\|_2^2$$



- **Corollary:** Suppose we use the FTRL algorithm with the squared L2-norm regularization $\frac{B^2}{2\eta}$ on an online linear optimization problem with $\mathcal{A} \subset \mathbb{R}^d$ such that

- $\sup_{\tilde{a} \in \mathcal{A}} \|\tilde{a}\|_2 \leq B$ for some finite constant $B > 0$,
- $\sup_{z \in \mathcal{Z}} \|z\|_2 \leq V$ for some finite constant $V > 0$.

Then, by choosing the step size η for FTRL as $\eta = \frac{B}{V\sqrt{2T}}$ it holds that

$$R_T^{FTRL} \leq BV\sqrt{2T}.$$

- Note that the (optimal) parameter η depends on the time horizon T , which is oftentimes not known in advance. However, there are some tricks (i.e., the *doubling trick*), which can help in such cases.



FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proof:**

- By the latter **proposition** and the **assumptions**

$$\begin{aligned} R_T^{\text{FTRL}}(\tilde{\mathbf{a}}) &\leq \frac{1}{2\eta} \|\tilde{\mathbf{a}}\|_2^2 && + \eta \sum_{t=1}^T \|z_t\|_2^2 \\ &\leq \frac{B^2}{2\eta} && + \eta T V^2. \end{aligned}$$



- The right-hand side of the latter display is independent of $\tilde{\mathbf{a}}$, so that

$$R_T^{\text{FTRL}} \leq \frac{B^2}{2\eta} + \eta T V^2.$$

FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proof:**

- By the latter **proposition** and the **assumptions**

$$\begin{aligned} R_T^{FTRL}(\tilde{a}) &\leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 && + \eta \sum_{t=1}^T \|z_t\|_2^2 \\ &\leq \frac{B^2}{2\eta} && + \eta T V^2. \end{aligned}$$

- The right-hand side of the latter display is independent of \tilde{a} , so that

$$R_T^{FTRL} \leq \frac{B^2}{2\eta} + \eta T V^2.$$

- Now, the right-hand side of the latter display is a function of the form $f(\eta) = a/\eta + b\eta$ for some suitable $a, b > 0$.



FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proof:**

- By the latter **proposition** and the **assumptions**

$$\begin{aligned} R_T^{FTRL}(\tilde{a}) &\leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 && + \eta \sum_{t=1}^T \|z_t\|_2^2 \\ &\leq \frac{B^2}{2\eta} && + \eta T V^2. \end{aligned}$$



- The right-hand side of the latter display is independent of \tilde{a} , so that

$$R_T^{FTRL} \leq \frac{B^2}{2\eta} + \eta T V^2.$$

- Now, the right-hand side of the latter display is a function of the form $f(\eta) = a/\eta + b\eta$ for some suitable $a, b > 0$.
- Minimizing f with respect to η results in the minimizer $\eta^* = \frac{B}{V\sqrt{2T}}$.

FTRL FOR OLO: THEORETICAL GUARANTEES

- **Proof:**

- By the latter **proposition** and the **assumptions**

$$\begin{aligned} R_T^{FTRL}(\tilde{a}) &\leq \frac{1}{2\eta} \|\tilde{a}\|_2^2 && + \eta \sum_{t=1}^T \|z_t\|_2^2 \\ &\leq \frac{B^2}{2\eta} && + \eta T V^2. \end{aligned}$$



- The right-hand side of the latter display is independent of \tilde{a} , so that

$$R_T^{FTRL} \leq \frac{B^2}{2\eta} + \eta T V^2.$$

- Now, the right-hand side of the latter display is a function of the form $f(\eta) = a/\eta + b\eta$ for some suitable $a, b > 0$.
- Minimizing f with respect to η results in the minimizer $\eta^* = \frac{B}{V\sqrt{2T}}$.
- **Plugging this minimizer into the latter display leads to the asserted inequality.** □

DESIRED RESULTS THEORETICAL GUARANTEES

Proof:

- With the FTRL algorithm we can cope with

- online quadratic optimization (OQO) problems by using no regularity ($\psi \equiv 0$). In this case, we have satisfactory regret guarantees and also a quick update rule for $\bar{a}_{t+1}^{\text{FTRL}}$ (It is just the empirical average over all data points seen till t),

$$\leq \frac{B^2}{2\eta} + \eta T V^2.$$

- The right-hand side of the latter display is independent of \bar{a} , so that

$$R_T^{\text{FTRL}} \leq \frac{B^2}{2\eta} + \eta T V^2.$$

- Now, the right-hand side of the latter display is a function of the form $f(\eta) = a/\eta + b\eta$ for some suitable $a, b > 0$.
- Minimizing f with respect to η results in the minimizer $\eta^* = \frac{B}{V\sqrt{2T}}$.
- Plugging this minimizer into the latter display leads to the asserted inequality. \square



DESIRED RESULTS

- With the FTRL algorithm we can cope with
 - online quadratic optimization (OQO) problems by using no regularity ($\psi \equiv 0$). In this case, we have satisfactory regret guarantees and also a quick update rule for $\bar{a}_{t+1}^{\text{FTRL}}$ (It is just the empirical average over all data points seen till t),
 - online linear optimization (OLO) problems by using a suitable regularization function. In this case, we have quick update formulas and satisfactory regret guarantees as well.



DESIRED RESULTS

- With the FTRL algorithm we can cope with
 - online quadratic optimization (OQO) problems by using no regularity ($\psi \equiv 0$). In this case, we have satisfactory regret guarantees and also a quick update rule for a_{t+1}^{FTRL} (It is just the empirical average over all data points seen till t),
 - online linear optimization (OLO) problems by using a suitable regularization function. In this case, we have quick update formulas and satisfactory regret guarantees as well.



⇒ But what about other online learning problems or rather other loss functions?

- What we wish to have is an approach such that we can achieve for a large class of loss functions the advantages of FTRL for OLO and OCO problems:
 - (a) reasonable regret upper bounds;
 - (b) a quick update formula.

DESIRED RESULTS

- With the FTRL algorithm we can cope with
 - online quadratic optimization (OQO) problems by using no regularity ($\psi \equiv 0$). In this case, we have satisfactory regret guarantees and also a quick update rule for a_{t+1}^{FTRL} (It is just the empirical average over all data points seen till t),
 - online linear optimization (OLO) problems by using a suitable regularization function. In this case, we have quick update formulas and satisfactory regret guarantees as well.

⇒ But what about other online learning problems or rather other loss functions?

- What we wish to have is an approach such that we can achieve for a large class of loss functions L the advantages of FTRL for OLO and OCO problems:
 - (a) reasonable regret upper bounds;
 - (b) a quick update formula.

