# **Applied Machine Learning**

Benchmarking:
Large-Scale Benchmarking & OpenML







## Learning goals

- Why Benchmarking?
- What is OpenML?

### WHY BENCHMARKING

It is hard to evaluate methods using theoretical/mathematical analysis alone.



- Theoretical analysis typically requires strong assumptions (e.g., infinite sample size, no noise, ideal model class).
- Implementation details cannot be formally compared through purely theoretical/mathematical analysis (e.g., runtime, memory use).
- Effect of different data properties on algorithms cannot be explained theoretically, e.g., does XGBoost outperform an LM on data with only categorical features?
- Hyperparameter settings are often not part of the theoretical analysis.

## THE STEPS OF BENCHMARKING

- Formulate a hypothesis (about algorithm performance or behavior)
- 2 Define an appropriate performance metric (if not part of the hypothesis)
- Select or collect datasets to evaluate the hypothesis
- Define a resampling strategy
- Define hyperparameter search space and tuning strategy
- Execute the full cross-product of learners, datasets, and tuning configurations
- Analyze results and draw conclusions

# THE PROBLEM WITH DATASETS

- No universally adopted standard dataset format
- No universally adopted dataset sharing platform
- Few platforms offer programmatic (API-based) access to data

# THE IDEAL WORLD - FRICTIONLESS ML

#### **Datasets**

- Unified access to all datasets via unified API
- Possibility to share own data (mostly relevant in academic context)
- Discover and search datasets via their meta-data

#### **Associated Objects**

- Tasks: Predefined train/test splits for standardized evaluation
- Runs: Publicly shared results (algorithm, settings, performance)




# OPENML - THE PROJECT • OpenML.org n.d.

• OpenML.org n.d. is not only a data repository, it is a collaborative ML platform for sharing individual **components** involved in benchmark experiments. **Benchmarking:** compare algorithms w.r.t. performance/runtime on datasets. **Goal:** Reproducibility, transparency, and large-scale collaboration in ML.

OpenML relies on 4 **basic components** (just like benchmark experiments):






## OPENML - THE PROJECT DenML.org n.d.

OpenML.org n.d. is not only a data repository, it is a collaborative ML platform for sharing individual **components** involved in benchmark experiments.

**Benchmarking:** compare algorithms w.r.t. performance/runtime on datasets. **Goal:** Reproducibility, transparency, and large-scale collaboration in ML.

OpenML relies on 4 basic components (just like benchmark experiments):

currently > 60.000



currently > 6.000



Supervised ML tasks contain:

data + target feature

performance measure

resampling technique (e.g., 10-fold CV) and train-test splits algorithm or a complex ML


pipeline that solves a task.

# OPENML - THE PROJECT • OpenML.org n.d.

• OpenML.org n.d. is not only a data repository, it is a collaborative ML platform for sharing individual **components** involved in benchmark experiments. **Benchmarking:** compare algorithms w.r.t. performance/runtime on datasets. **Goal:** Reproducibility, transparency, and large-scale collaboration in ML.

OpenML relies on 4 **basic components** (just like benchmark experiments):





Note: OpenML also supports collections of tasks and runs

#### **OPENML DATASETS**

- Raw data stored in standardized formats:
  - .arff (Attribute-Relation File Format): plain-text format with inline schema
  - .parquet: efficient binary columnar storage (preferred for large data)



- Dataset description (source, intended use, licensing)
- Feature names and types (numeric, categorical, ordinal, date, string)
- Designated roles: input features, target variable, ignored columns

#### • Automatically extracted information:

- Meta-features (e.g., number of instances, number of features)
- Statistical summaries (missing values, sparsity, imbalance)
- Baseline performance of simple models (e.g., majority class classifier)



### **OPENML TASKS**

- A task defines a concrete ML problem on a dataset, e.g., in supervised ML:
  - Target feature (to be predicted)
  - Resampling strategy (e.g., 10-fold CV, holdout)
  - Evaluation metric (e.g., accuracy, RMSE)
- Tasks ensure reproducibility by fixing all relevant components
- Flows (i.e., ML pipelines or learners) are executed on tasks and produce runs



# **OPEN QUESTION: WHAT DATASETS/TASKS TO USE?**

- Hard to compare results across papers
- Benchmarking is often done on small set of datasets
  - Question about generalization to other datasets
  - Cherry picking or arbitrary selection
  - Different versions, different train-test setups
- Publication bias
  - Published papers report good results
  - Interesting to know WHEN an algorithm works (and when it doesn't)



# **OPENML BENCHMARKING SUITES**



- Benchmarking suite: curated collection of standardized OpenML tasks
- Provide unified, shareable task definitions with fixed resampling and target
- Accessible via APIs in R, Python, and Java
- Enable reproducible and comparable experiments toward shared research goals

# **EXAMPLE I: OPENML-CC18 (CLASSIFICATION)**

▶ "Bischl et al." 2021

Standardized benchmark suite for evaluating supervised classification algorithms.

- 72 classification tasks
- Medium size: 500−100,000 observations, ≤ 5000 features (post encoding)
- Contains missing values and categorical features
- Excludes:
  - Strong class imbalance
  - Time series or group structure
  - Sparse data and free-form text
- Follows objective and subjective selection criteria (see paper)



# **EXAMPLE II: OPENML-CTR23 (REGRESSION)**

▶ "Fischer et al." 2023



Extension of CC18 selection principles to regression tasks.

- Uses same structural filters as CC18
- Includes only datasets with numeric targets and ≥ 5 distinct values
- Excludes:
  - Datasets trivially solved by linear models
  - Datasets with ethical/legal concerns
  - Datasets restricted from public benchmarking

# **EXAMPLE III: AUTOML BENCHMARK SUITE (AMLB)**

▶ "Gijsbers et al." 2024



Designed to evaluate modern AutoML systems on realistic and diverse problems.

- 71 classification tasks and 33 regression tasks
- Stricter inclusion criteria for difficulty and real-world complexity
- Covers multiple domains; avoids trivial, overly cleaned, or synthetic data
- Excludes:
  - Free-text features
  - Time dependencies or metadata leaks

# WHY PARALLELIZATION MATTERS

#### Benchmark Scenario (AutoML Study)

- 71 datasets × 10-fold cross-validation
- 9 AutoML systems evaluated
- 1 hour per system-dataset-fold combination
- ⇒ Total runtime: **6390 hours** = **266+ days** sequentially

**Conclusion:** Benchmarking at scale is infeasible without parallelization.

