Algorithms and Data Structures

Numerics Condition in systems of linear equations (LES)





Learning goals

- Matrix multiplication
- LES
- Sherman-Morrison formula
- Woodbury formula

CONDITION NUMBER: MATRIX MULTIPLICATION

Although we are actually interested in $\mathbf{x} = \mathbf{A}^{-1}\mathbf{y}$, we first consider the direct problem: $\mathbf{y} = \mathbf{A}\mathbf{x}$.

Since

$$y_i = \sum_{j=1}^n A_{ij} x_j,$$

it is to be expected that the high condition number of the addition is also transferred to **Ax**.

× < 0 × × ×

CONDITION NUMBER: MATRIX MULTIPLICATION / 2

When **A** and **x** are disturbed by Δ **A** and Δ **x**, the **absolute error** in the result **y** is:

$$\begin{array}{rcl} \mathbf{y} + \Delta \mathbf{y} &=& (\mathbf{A} + \Delta \mathbf{A})(\mathbf{x} + \Delta \mathbf{x}) \\ &=& \mathbf{A}\mathbf{x} + \Delta \mathbf{A}\mathbf{x} + \mathbf{A}\Delta \mathbf{x} + \Delta \mathbf{A}\Delta \mathbf{x} & |-\mathbf{y} \\ \Delta \mathbf{y} &=& \Delta \mathbf{A}\mathbf{x} + \mathbf{A}\Delta \mathbf{x} + \Delta \mathbf{A}\Delta \mathbf{x} \end{array}$$

The absolute error is therefore estimated as follows

× 0 0 × × ×

CONDITION NUMBER: MATRIX MULTIPLICATION / 3

From the estimate for the absolute error, we obtain

$$\begin{split} \|\Delta \mathbf{y}\| &\leq \|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\| \\ &= (\|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|) \frac{\|\mathbf{x}\|}{\|\mathbf{x}\|} \\ &= (\|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|) \frac{\|\mathbf{A}^{-1}\mathbf{y}\|}{\|\mathbf{x}\|} \\ &\leq (\|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|) \frac{\|\mathbf{A}^{-1}\| \|\mathbf{y}\|}{\|\mathbf{x}\|} \\ &= \left(\frac{\|\mathbf{A}\|}{\|\mathbf{A}\|} \|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|\right) \frac{\|\mathbf{A}^{-1}\| \|\mathbf{y}\|}{\|\mathbf{x}\|} \\ &= \left(\frac{\|\mathbf{A}\|}{\|\mathbf{A}\|} \|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|\right) \frac{\|\mathbf{A}^{-1}\| \|\mathbf{y}\|}{\|\mathbf{x}\|} \\ &= \left(\frac{\|\mathbf{A}\|}{\|\mathbf{A}\|} \|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\Delta \mathbf{x}\|\right) \frac{\|\mathbf{A}^{-1}\| \|\mathbf{y}\|}{\|\mathbf{x}\|} \\ &= \left(\frac{\|\mathbf{A}\| \|\mathbf{A}^{-1}\|}{\|\mathbf{A}\| \|\mathbf{x}\|} \|\Delta \mathbf{A}\| \|\mathbf{x}\| + \|\mathbf{A}\| \|\mathbf{A}^{-1}\| \frac{\|\Delta \mathbf{x}\|}{\|\mathbf{x}\|}\right) \|\mathbf{y}\| \\ \frac{\|\Delta \mathbf{y}\|}{\|\mathbf{y}\|} &\leq \|\mathbf{A}\| \|\mathbf{A}^{-1}\| \left(\frac{\|\Delta \mathbf{A}\|}{\|\mathbf{A}\|} + \frac{\|\Delta \mathbf{x}\|}{\|\mathbf{x}\|}\right). \end{split}$$

× 0 0 × × ×

CONDITION NUMBER: MATRIX MULTIPLICATION / 4

The condition number

$$\kappa(\mathbf{A}) = \|\mathbf{A}\| \|\mathbf{A}^{-1}\|$$

describes the propagation of relative errors both in the matrix and on the right side of the LES.

Example:

$$\mathbf{y} = \mathbf{A}\mathbf{x}, \quad \mathbf{A} = \begin{pmatrix} 1 & 1 \\ 1 & 1 + \epsilon \end{pmatrix}, \quad \mathbf{x}^{T} = \begin{pmatrix} 1 & -1 \end{pmatrix}$$
$$\|\mathbf{A}\|_{\infty} = 2 + \epsilon, \quad \mathbf{A}^{-1} = \frac{1}{1 + \epsilon - 1} \begin{pmatrix} 1 + \epsilon & -1 \\ -1 & 1 \end{pmatrix}, \quad \|\mathbf{A}^{-1}\|_{\infty} = \frac{2 + \epsilon}{\epsilon}$$
$$\kappa(\mathbf{A}) = (2 + \epsilon) \frac{2 + \epsilon}{\epsilon} = \frac{4 + 4\epsilon + \epsilon^{2}}{\epsilon} \approx \frac{4}{\epsilon} \quad \text{and} \quad \epsilon \ll 1.$$

 $\epsilon = 10^{-8}$ and machine epsilon eps = 10^{-16} in **x** result in a relative precision of just about $4/10^{-8} \cdot 10^{-16} = 4 \cdot 10^{-8}$ in **y**.

× × ×

CONDITION NUMBER: LES

The solution of the LES $\mathbf{x} = \mathbf{A}^{-1}\mathbf{y}$ is (numerically) equivalent to the results of the matrix multiplication. The following applies

$$\kappa(\mathbf{A}) = \|\mathbf{A}\| \|\mathbf{A}^{-1}\| = \kappa(\mathbf{A}^{-1}).$$

Note:

$$\kappa(\mathbf{A}) = \|\mathbf{A}\| \|\mathbf{A}^{-1}\| \ge \|\mathbf{A}\mathbf{A}^{-1}\| = \|\mathbf{I}\| = 1.$$

Example 1:

Consider the matrix
$$\mathbf{A} = \begin{pmatrix} 1 & 1 \\ 1 + 10^{-10} & 1 - 10^{-10} \end{pmatrix}$$

The matrix is ill-conditioned with condition number $\kappa \approx 2 \times 10^9$. For the solution of the LES Ax = y this means: a small variation in the input data (e.g. $y = (1, 1) \rightarrow \tilde{y} = (1, 1.00001)$) leads to a big change in the solution.



CONDITION NUMBER: LES / 2

```
A = matrix(c(1, 1 + 10e-10, 1, 1 - 10e-10), nrow = 2)
y = c(1, 1)
yt = c(1, 1.00001)
```

solve(A, y)
[1] 0.4999999722444252 0.5000000277555748

```
solve(A, yt)
## [1] 5000.499858862901 -4999.499858862901
```

× 0 0 × 0 × ×

CONDITION NUMBER: LES / 3

Example 2: The Hilbert matrix is known to be ill-conditioned!

$$H_{ij}=\frac{1}{i+j-1},$$

```
hilbert = function(n) {
    i = 1:n
    return(1 / outer(i - 1, i, "+"))
}
hilbert(4)
```

× 0 0 × × ×

CONDITION NUMBER: LES / 4

##		[,1]	[,2]
##	[1,]	1.000000000000000000000000000000000000	0.500000000000000000000000000000000000
##	[2,]	0.5000000000000000	0.3333333333333333333
##	[3,]	0.33333333333333333333	0.2500000000000000
##	[4,]	0.2500000000000000	0.2000000000000000
##		[,3]	[,4]
##	[1,]	0.33333333333333333333	0.2500000000000000
##	[2,]	0.2500000000000000	0.2000000000000000
##	[3,]	0.2000000000000000	0.166666666666666
##	[4.]	0.1666666666666666	0.1428571428571428

× × 0 × ×

CONDITION NUMBER: LES / 5

```
foo = function(n) {
 cond = sapply(n, function(i) {
   norm(hilbert(i)) * norm(solve(hilbert(i)))
 })
 return(cbind(n, cond))
}
foo(4:10)
##
                           cond
        n
## [1,] 4 2.837499999999738e+04
## [2,] 5 9.43655999999363e+05
## [3,] 6 2.907027900294877e+07
## [4,] 7 9.851948897194694e+08
## [5,] 8 3.387279082022739e+10
## [6,] 9 1.099650993366049e+12
## [7,] 10 3.535372424347476e+13
```

× 0 0 × 0 × ×

WELL- VS. ILL-POSED PROBLEMS

A problem is called well-posed if the following holds:

- There exists a solution for the problem
- The existing solution is unique
- The solution depends continuously on the condition of the problem (stable)

A problem is called ill-posed if it violates at least one of these properties. However, the instability of solutions usually causes the most difficulties. × < 0 × × ×

"DO NOT INVERT THAT MATRIX"

Important: Never solve an LES (numerically) using $\mathbf{x} = \mathbf{A}^{-1}\mathbf{y}$.

solve(A) %*% y

Although theoretically correct, internally **two** (possibly ill-posed) problems are solved:

- Inversion of **A** (solution of Ax = 0) has a condition of $||A|| ||A^{-1}||$
- The multiplication of $\textbf{A}^{-1} \cdot \textbf{y}$ has a condition of $\|\textbf{A}\| \| \textbf{A}^{-1} \|$

The condition inflates: $\|\boldsymbol{A}\|^2 \|\boldsymbol{A}^{-1}\|^2$



"DO NOT INVERT THAT MATRIX" / 2

Better: Solve directly by

solve(A, y)

Advantages:

- Stability: In the worst case only one ill-posed subproblem is solved.
- Memory: The n² entries of the inverted matrix A⁻¹ must be saved. With a direct solution via the LES only x ∈ ℝⁿ is stored (¹/_n-th of storage space).

Systems of equations can be solved efficiently and numerically stable by means of matrix decompositions (more on this in chapter 7 - matrix decompositions).



SHERMAN-MORRISON FORMULA

If a matrix **X** can be represented by $\mathbf{X} = \mathbf{A} + \boldsymbol{u}\boldsymbol{v}^{T}$, \mathbf{X}^{-1} can be calculated using the **Sherman-Morrison formula** as follows:

$$\boldsymbol{X}^{-1} = (\boldsymbol{A} + \boldsymbol{u}\boldsymbol{v}^{T})^{-1} = \boldsymbol{A}^{-1} - \frac{\boldsymbol{A}^{-1}\boldsymbol{u}\boldsymbol{v}^{T}\boldsymbol{A}^{-1}}{1 - \boldsymbol{v}^{T}\boldsymbol{A}^{-1}\boldsymbol{u}}$$

Proof:

$$X \cdot X^{-1} = (\mathbf{A} + uv^{T})(\mathbf{A}^{-1} - \frac{\mathbf{A}^{-1}uv^{T}\mathbf{A}^{-1}}{1 - v^{T}\mathbf{A}^{-1}u})$$

= $\mathbf{A}\mathbf{A}^{-1} + uv^{T}\mathbf{A}^{-1} - \frac{\mathbf{A}\mathbf{A}^{-1}uv^{T}\mathbf{A}^{-1} - uv^{T}\mathbf{A}^{-1}uv^{T}\mathbf{A}^{-1}}{1 - v^{T}\mathbf{A}^{-1}u}$
= $\mathbf{I} + uv^{T}\mathbf{A}^{-1} - \frac{uv^{T}\mathbf{A}^{-1} - uv^{T}\mathbf{A}^{-1}uv^{T}\mathbf{A}^{-1}}{1 - v^{T}\mathbf{A}^{-1}u}$
= $\mathbf{I} + uv^{T}\mathbf{A}^{-1} - \frac{u(1 - v^{T}\mathbf{A}^{-1}u)v^{T}\mathbf{A}^{-1}}{1 - v^{T}\mathbf{A}^{-1}u}$
= $\mathbf{I} + uv^{T}\mathbf{A}^{-1} - \frac{uv^{T}\mathbf{A}^{-1} - uv^{T}\mathbf{A}^{-1}u}{1 - v^{T}\mathbf{A}^{-1}u}$

× < 0 × × ×

WOODBURY FORMULA

If a matrix **X** can be represented by $\mathbf{X} = \mathbf{A} + \mathbf{UCV}$, \mathbf{X}^{-1} can be calculated using the **Woodbury formula** as:

$$X^{-1} = (A + UCV)^{-1} = A^{-1} - A^{-1}U(C^{-1} + VA^{-1}U)^{-1}VA^{-1}$$

The formula is especially useful if \mathbf{A}^{-1} is very easy to calculate or has already been calculated.

The Woodbury formula is often used in optimization (low-rank updates, BFGS updates). See Chapter 10 (Multivariate Optimization) for more information.

